



1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26

Linux based 3G Specification

Multimedia Mobile Phone API

Preface

Document: CELF_MPP_Preface_FR1_20060301

WARNING : This is a working draft for review only, it is NOT a published specification of the CE Linux Forum. It is likely that further substantial changes will be made in the course of review and issue resolution. Send comments on this version to:

MppApiComments@tree.celinuxforum.org

27 **Revision History**

Revision	Comment	Reviewer	Editor	Date
2.2	Prepared for Tamagawa meeting		NEC, Panasonic	2005.9.28
2.2.1	Prepared for San Francisco meeting, new format		Scott Preece	2005.10.31
2.2.3	Integrated issue resolutions from Reference Architecture and added Common Types and Programming Model sections.		Scott Preece	2005.12.20
2.2.4	Updated to clarify that Application ID and Client ID are the same thing.		Scott Preece	2006.2.1
FR1	First version for Formal Review		Scott Preece	2006.3.1

28	0. Introduction.....	4
29	0.1.1 Circuit Switched Communication Service.....	4
30	0.1.2 Packet Switched Communication Service.....	4
31	0.1.3 Short Message Service.....	4
32	0.1.4 Equipment Service.....	4
33	0.2 Structure of API Documents.....	4
34	0.2.1 Introduction Section.....	4
35	0.2.2 Primitives Section.....	4
36	0.2.3 Functions Section.....	4
37	0.3 Terminology and abbreviations.....	5
38	0.4 References.....	9
39	0.4.1 Normative.....	9
40	0.4.2 Informative.....	9
41	1. Programming Model.....	10
42	1.1 Events and Notifications.....	10
43	1.1.1 Spontaneous Events.....	10
44	1.1.2 Result Events.....	10
45	1.1.3 Application IDs.....	10
46	1.1.4 Callback Notification Functions.....	10
47	1.1.5 Registering.....	10
48	1.2 Synchronous Service Interfaces.....	11
49	1.3 Asynchronous Service Interfaces.....	11
50	2. Common Primitives.....	12
51	2.1 Constants.....	12
52	2.2 Enums.....	12
53	2.2.1 CelfMpStatus.....	12
54	2.3 Data Types and Structures.....	12
55	2.3.1 CelfMpCallRef.....	12
56	2.3.2 CelfMpEvent.....	12
57	2.3.3 CelfMpCallback.....	13
58	2.3.4 CelfMpAppId.....	13
59		

60 **0. Introduction**

61 This Preface to the CELF Mobile Phone API describes the sections of the API specification of the
62 Telephony Service for 3G multimedia mobile telephone based on Linux. It also provides an introduction to
63 some common concepts and terminology used in the Specifications and defines some common datatypes.

64 This document is the work of the CE Linux Forum's Mobile Phone Profile Working Group [MPPWG].

65 The major sections of the Telephony API are described below.

66 **0.1.1 Circuit Switched Communication Service**

67 The Circuit Switched Communication Service (CS Service) API provides access to functionality for call
68 control, call state management, tone control, and log processing. This chapter includes the Voice
69 communication service, the Video communication service, and the Unrestricted Digital data
70 Communication service.

71 **0.1.2 Packet Switched Communication Service**

72 The Packet Switched Communication Service (PS Service) API provides access to functionality for packet
73 call control and for sending and receiving data packets. This chapter includes the PPP dial-up
74 communication service and the IP connection data transfer service.

75 **0.1.3 Short Message Service**

76 The Short Message Service (SMS Service) API provides access to functionality for sending and receiving
77 messages using the SMS protocol.

78 **0.1.4 Equipment Service**

79 The Equipment Service API provides access to functionality for setting and reading various status
80 information and operating modes of the handset (Earphone mode, Manner mode, Dial call restriction,
81 Battery level, etc.).

82 **0.2 Structure of API Documents**

83 Each chapter defines the API for a major sub-area of functionality. The content of each chapter is divided
84 into:

- 85 1. Introduction – An overview of the service, placing it in context.
- 86 2. Primitives – Definitions of the data types, constants, and enumerations used in the API definitions.
- 87 3. Functions – Definitions of the individual functional interfaces provided by the service.

88 **0.2.1 Introduction Section**

89 An Introduction to the functionality available through the API of the service described by the chapter.

90 **0.2.2 Primitives Section**

91 This section is subdivided into sub-sections for Data Types and Structures and for Constants. In each case,
92 the primitive is named, its use is described, and its formal definition (as would appear in a header file) is
93 given.

94 **0.2.3 Functions Section**

95 Each function appears as a separate section. The information given for each function includes:

- | | |
|-----------|--|
| 96 Symbol | The formal (programming) name of the function. |
| 97 Syntax | Syntax used in programming in C language |

- 98 Argument Arguments of API function in C language
- 99 Return value Return value of API function in C language
- 100 Include file File name to be included in Programming
- 101 Functional description Definition and detail explanation of API function

0.3 Terminology and abbreviations

The following words, phrases, and acronyms have specific meanings within the context of the API.

word	explanation
32K AV communication	Communication mode with AV at the speed of 32Kbps
32K data communication	Data communication mode at a stable communication speed of 32Kbps. Unlimited digital 32K communication.
64K AV communication	Communication mode with AV at the speed of 64Kbps
64K data communication	Data communication mode at a stable communication speed of 64Kbps. Unlimited digital 64K communication.
accumulated reset	Resetting of the accumulated duration data. The handset stores data on the total duration of all calls .
API	Application Program Interface
App or Application	Application program; a program run in user space.
ASF	Advanced Streaming Format
automatic incoming call	Operating mode in which the handset automatically accepts incoming calls, without the user accepting each call by a manual operation..
automatic transmission	Placing a call by keying in all the digits and then initiating the connection. Same as “on-hook originating”.
call duration	The duration of a voice call.
call quality alarm	The indication that radio reception from the network has deteriorated and the call is likely to be dropped.
call reference	An identifier for a particular call. This identifier is assigned by the network or mobile phone, and used in the call-management APIs to operate on a particular.
CS	Circuit Switched operation; a mode of communication in which a dedicated channel is maintained between the handset and the remote party and the call content is routed over that identified channel.

Classification: Mobile Phone API

DCF	Device Control Function. The module that provides the following functions: <ul style="list-style-type: none"> • Mobile phone control via AT commands. • Monitoring S-IF message and notice status change event to service. • To notice MTF (block which exchange message between TAF-NW) when sets up receive denial.
DTMF	Dual Tone Multi Frequency. The tones generated to correspond to key presses while a CS connection is open (off-hook originating). On digital connections, the tones may be represented by designated codes rather than encoded audio.
Earphone (external option)	Controls whether audio is routed to an attached earphone (headset) or to a built-in loudspeaker.
emergency originating restriction	A network condition in which call from handsets are not accepted because an emergency requires all of the available network capacity..
Engine	Application Engine; a software module providing “backend” processing to support a service interface.
external AV communication	Videophone communication using a USB connection cable, etc., to connect terminal and external equipment (such as a PCⓂpersonal computer) to the handset).
FLASH	Macromedia Flash Player; the engine that execute Flash programs.
high priority communication mode	The display mode in which an alert or icon is displayed in case of <ul style="list-style-type: none"> (a) an incoming packet switched communication when circuit switched communication is active, or (b) an incoming circuit switched communication when packet switched communication is active.
hold tone	A tone or melody that sounds when a voice call or AV call is changed to hold status.
HTTP	Hyper Text Transfer Protocol
I/F	Interface
IMEI	IMEI (International Mobile Station Equipment Identity). A unique number allocated to each individual mobile station (handset).
internal AV communication	Videophone communication between terminals.
IR	Infra-Red
JAM	Java Application Manager
JVM	Java Virtual Machine

Kernel	Linux Kernel
keypad dial lock	When this function is set, the handset does not allow voice or videophone calls by dialing phone numbers, extension number, or SIP. Dialing from previously stored "Phonebook" entries and from the "Dialed calls" or "Redial" entries remains possible.
LCD	Liquid Crystal Display
Low-voltage alarm	The alarm sounded to indicate that the battery is about to run out of power.
manner mode	Manner mode provides a quick and convenient way of muting the terminal's ring tones and keypad sound to avoid disturbing people around you.
manual transmission	Same as off-hook originating
MAW	Monitoring and Watching
MSB	Mobile Software Bus
multiple calls	It is the combination of maximum three call. The conversation, hold and incoming call is at most one call.
noise canceller	A function that reduce ambient transmitted over a connection so that the other party can hear the voice more clearly.
normal originating restriction	When this mode is set, outgoing calls are permitted only to designated special numbers.
number notification	On option that determines whether the handset's telephone number is sent to the other party when a call is initiated.
OBEX	Object Exchange protocol
OCR	Optical Character Recognition
off-hook originating	Placing a call by keying the digits after pressing the start button; when five seconds have elapsed since the last input digit the call is initiated.
on-hook originating	Placing a call by pressing the start button after inputting all dial digits.
out-of-communication area	The mode of operation when the handset is unable to establish communication with the network because it is out of the service area or the signal is too weak or there is no network with which the handset is allowed to register.
phone-answering message	A message sent to the calling party when the handset can not respond to an incoming call.
phone-answering message service	A network-side service that provides for recording messages from callers when the handset is not in service..

Classification: Mobile Phone API

PIM lock	A handset mode in which the user has indicated that no access is allowed to personal-information resources, such as "Phonebook", "Schedule", "Mail", "Messenger", and "Presence".
PIN	Personal Identification Number
PS	Packet Switched network
receive level	The receive level is the strength of the radio signal received from the network.
reconnection tone	The tone that sounds when the handset reconnects to the network after being out of service.
SCA	Stream Control API
SD	SD memory card
SDFS	SD File System
secret mode	A handset mode that controls whether personal information resource display or hide those entries that have been marked by the user as secret.
SMS	Short Message Service
special number	A number to connect with a service center in the network.
SS	A Supplementary network service accessible using the SS protocol, which encodes a service code as a four-part data string starting with '*', '#', or '*#' and ending with '#'. The service code is either a standardized 3GPP code or a code defined by operator (USSD).
SSL	Secure Socket Layer
supplementary service	An optional service provided by the network and available to the handset through special signalling.
TAF	Terminal Adaptation Function. The module that connects handset functions to communication services.
UIM	Same as USIM (Universal Subscriber Identity Module).The removable hardware module that contains information identifying a network account plus various kinds of user-defined information (phone book entries, messages, service-specific information, applications, etc.).
USSD	Unstructured Supplementary Service Data a network- specific supplementary service code.
WDC	Watching Device Condition
within-communication area	The condition when the handset is in service area and able to communicate with the network.

104

105 **0.4 References**

106 0.4.1 Normative

107

108 0.4.2 Informative

DRAFT

109 1. Programming Model

110 The MPP API defines both synchronous and asynchronous interfaces. Synchronous interfaces return a
111 result directly to the calling program, whose execution is blocked until the function returns. Asynchronous
112 interfaces return a result directly, but the result indicates only whether the request was successfully
113 initiated. The actual result of an asynchronous service request is received as an event notification sometime
114 after the request has been made. Asynchronous operations are used when the delay involved in processing a
115 request is likely to be long for the client to block and be unable to do other work.

116 1.1 Events and Notifications

117 MPP API clients can register to receive notification when specified events occur. The notification is
118 delivered through a call by the service to a function specified by the client when the request for notification
119 was registered.

120 The event-delivery model is widely used throughout the interface, both for delivering the results of
121 asynchronous service requests (“result events”) and for notifying clients of events that occur in the system
122 (“spontaneous events”). For instance, a client can register to receive notification when an incoming call
123 arrives from the network.

124 1.1.1 Spontaneous Events

125 Spontaneous events are the means by which clients become aware of activities of the network or of
126 anomalous situations in the device (such as low battery conditions). Spontaneous-event notifications are
127 multicase: when a spontaneous event occurs, the MPP server calls the notification callback functions of all
128 clients that have requested notification of the given event.

129 1.1.2 Result Events

130 Result events are the means by which clients receive the results of asynchronous operations. When the
131 server completes processing of an asynchronous service request, it calls the notification callback function
132 most recently registered for that event. Each time a client registers for a result event, the server drops any
133 previous registration for that event.

134 1.1.3 Application IDs

135 In order for events to be delivered to the right client, each client provides an application ID (client ID) to
136 the server when it registers for notifications. The ID is a unique integer value associated with each
137 application or server that needs to receive events. No special semantics are associated with the value, but it
138 must be unique for each client.

139 1.1.4 Callback Notification Functions

140 When an event occurs, the MPP server calls the callback notification function(s) registered for that event.
141 The function is called with one argument, a pointer to a CelfMpEvent structure, which contains a fixed part
142 with members that identify the type and subtype of the event and an open part that contains data fields
143 appropriate to the specific event type.

144 The function is called in the process context of the client, so the client’s internal namespace is available in
145 writing the function. The method by which the system arranges for the process to be called in the client’s
146 context is outside the scope of the API definition.

147 1.1.5 Registering

148 A client requests notification of particular events by calling a registration function (which usually has a
149 name that starts with “start” and ends with “notification”), providing a client ID, event mask, and call back
150 function pointer as arguments. The event mask indicates which of the events provided by the particular
151 service the client is requesting notification for. There is a separate notification_..._start() function for each

152 cluster of services in the MPP API; for instance, the SMS service has a registration service separate from
153 the packet-switched communications service.

154 **1.2 Synchronous Service Interfaces**

155 The processing of a synchronous request looks to the client like any other normal function call. The
156 implementation may do special processing to pass associated data between the client's process context and
157 the MPP server's process context, but that is outside the definition of the API. The client process is blocked
158 during the processing of the request and resumes execution with the assignment of the provided result into
159 the given variable (if appropriate).

160 **1.3 Asynchronous Service Interfaces**

161 To use an asynchronous service, the client must first call an interface to register to receive the notifications
162 associated with the service to be requested. The registration request would include a list of the events
163 requested and the callback function the server should call when the given events occur. A client may
164 register different callbacks for different events provided by the same service.

165 When the client makes an asynchronous request, it receives a result from that function call that indicates
166 whether the server accepted the request successfully. The client can then continue doing whatever
167 processing it has to do or can block waiting for the result to come back through a call to one of the callback
168 notification functions that it has registered.

169 When an event occurs (either completion of a service request or a spontaneous event), the MPP server will
170 check to see whether any clients are registered for that event and, if so, will arrange for the callback
171 notification functions that those clients registered against the event to be called in the application process
172 context.

173 2. Common Primitives

174 This section documents data types and values used throughout the sections of the API specification.

175 2.1 Constants

176

177 2.2 Enums

178 2.2.1 CelfMpStatus

179 **Description:** Status returned by MPP API functions

180

181 **Definition:**

182 CELF_MP_STATUS_OK: Successful completion

183 CELF_MP_STATUS_APP_ID_ERR: Invalid Application ID

184 CELF_MP_STATUS_EVENT_SET_ERR: The set of event is invalid

185 CELF_MP_STATUS_CALL_REF_ERR: Invalid Call reference

186

187 CELF_MP_STATUS_PS_PDP_TYPE_ERR: Unsupported PDP type

188 CELF_MP_STATUS_PS_DENIED: Request rejected by network due to no
189 subscription to packet communication service

190

191 CELF_MP_STATUS_ERR: Other error

192

193

194 2.3 Data Types and Structures

195 2.3.1 CelfMpCallRef

196 **Description:** Call Reference for the current call

197

198 **Definition:** `typedef unsigned char CelfMpCallRef;`

199

200 2.3.2 CelfMpEvent

201 **Description:** MPP notification events structure

202

203 **Definition:**

204

```
205 typedef struct {
206     int    category ;
207     int    subtype ;
208     int    info ;
209     int    subinfo ;
210     union {
211         ...
```

```
212         messages structures
213         ...
214     } data ;
215 } CelfMpEvent;
216
```

217 2.3.3 CelfMpCallback

218 **Description:** Pointer to a callback function

219

220 **Definition:** typedef void (* CelfMpCallback)();

221

222 2.3.4 CelfMpAppId

223 **Description:** Application ID

224

225 **Definition:** typedef int CelfMpAppId;

226

227

